



Wireless Water Sensor

Technical Overview

General Description

The OEM RF Wireless Water Sensor detects the presence or non-presence of water.

Features

- 3 ft. lead wires.
- Immediately detects water.

Principle of Operation

The OEM Wireless Water Sensor detects when water is present by completing the circuit between the two lead wires. When water is present the sensor will immediately turn on the RF radio and transmit the data to the wireless gateway and sensor monitoring software, allowing the user to immediately receive an SMS text or email alert. The sensor can be configured to detect both the presence and non-presence of water.

OEM Sensor Core Specifications

- Power: 3.0 V coin cell battery
- Communication: RF 900, 868 and 433 MHz
- Antenna: 4" wire antenna
- Operating Temperature: -40° to 85°C (-40° to 185°F)
- Device Range: 250 - 300 ft. non-line-of-sight*
- Only 1 inch by 1 inch

* Actual range may vary depending on environment.

Applications

- Water heater monitoring.
- Plumbing leak detection.
- Sump monitoring.
- Boat bilge monitoring.
- Reservoir level monitoring.

Specifications

Supply Voltage	2.0 - 3.6 VDC *
Current Consumption	0.7 μ A (sleep mode) 2 mA (radio idle/off mode) 2 mA (measurement mode) 25 mA (radio RX mode) 35 mA (radio TX mode)
Operating Temperature Range	-40°C to +85°C (-40°F to +185°F) **
Optimal Battery Temperature Range (Coin Cell)	+10°C to +60°C (+50°F to +140°F)
Lead Wire Length	3 ft. (36 in.)
Detection Wires	High Impedance

* Hardware can not withstand negative voltage. Please take care when connecting a power device.

** At temperatures above 100°C, it is possible to lose programmed memory.

For more product information, to get a quote, or to place an order, please contact our sales department at 801-561-5555. Visit us on the web at www.oemsensors.com.