



Wireless Activity Sensor

Technical Overview

General Description

The OEM RF Wireless Activity Sensor detects vibration or sudden movement.

Features

- Detects vibration or sudden movement.

Principle of Operation

The OEM Wireless Activity Sensor uses a vibration sensor to detect movement of the device. If the sensor detects movement it sends the information to the sensor monitoring software. The data is stored in the software and can be reviewed and exported as a data sheet or graph. Notifications can be set up to alert the user immediately when movement is detected with the ability to only notify within time of day parameters.

OEM Sensor Core Specifications

- Power: 3.0 V coin cell battery
- Communication: RF 900, 868 and 433 MHz
- Antenna: 4" wire antenna
- Operating Temperature: -40° to 85°C (-40° to 185°F)
- Device Range: 250 - 300 ft. non-line-of-sight*
- Only 1 inch by 1 inch

* Actual range may vary depending on environment.

Applications

- Machinery monitoring.
- Pump monitoring.
- Detect if a window is broken or shattered.

Specifications

Supply Voltage	2.0 - 3.6 VDC *
Current Consumption	0.7 μ A (sleep mode) 2 mA (radio idle/off mode) 2 mA (measurement mode) 25 mA (radio RX mode) 35 mA (radio TX mode)
Operating Temperature Range	-40°C to +85°C (-40°F to +185°F) **
Optimal Battery Temperature Range (Coin Cell)	+10°C to +60°C (+50°F to +140°F)
Sensor Power Consumption	0.25 μ A continuous
Sensitivity	0.05 g
Compliance	RoHS compliant

* Hardware can not withstand negative voltage. Please take care when connecting a power device.

** At temperatures above 100°C, it is possible to lose programmed memory.

For more product information, to get a quote, or to place an order, please contact our sales department at 801-561-5555. Visit us on the web at www.oemsensors.com.